



RayTec IRL-VAR2-i2-1

Vario2 i2, single panel, 78m, 850nm, 12V-24V AC/DC input, 10W

Description

VARIO2 illuminators use PLATINUM Elite SMT LED technology to deliver more power and greater distances from a smaller platform than current generation illuminators. Providing a broader range of solutions, the VARIO2 series also offers a suite of advanced security features for easier programming and safer operation of smart lighting systems.

VARIO2 features an interchangeable lens system with Hot-spot Reduction Technology to deliver highly even illumination, where it is most needed, for outstanding night-time images. With the optional hand-held remote control, VARIO2 also makes installation and commissioning quicker, easier and safer.

Features

- Distances up to 78m (256ft)
- PLATINUM Elite SMT LED Technology
- Hot-spot Reduction Technology (HRT)
- VARIO Interchangeable Lens System
- VARIO Remote Control (optional)
- Angles from 10-120 degrees – from 1 product
- Semi-Covert (850nm) or Covert (940nm - optional)
- Advanced Security Settings

Specs

ILLUMINATOR

Max Distance	78 m (256ft)
Angle	Standard pack includes 10° circular +35° x 10° (fitted as standard) and 60° x 25° elliptical lenses
Optics	Platinum Elite SMT LEDs
Consumption	10W max
Input	12/24V AC/DC
Weight	600g (1.3lbs)
Environmental	IP66
Temp Range	-50 to +50°C (-58 to 122°F)
Cable Length	2.5m
Colour	Black
Wavelength	850 or 940nm (optional)
Dimensions	75 x 100 x 64mm 3 x 4 x 2.5 approx
BRACKETRY	U Bracket included.

Integrated Standard Features

Power adjust from 20-100%
In-built photocell for automatic on/off operation
Photocell following output
Photocell sensitivity adjust
LED status indicator provides status on performance of the unit
LED status indicator on/off
Disable programming mode
Timer function (up to 30 mins)
Telemetry control
Remote Dimming
Restore factory default settings
Optional PIN to lock in settings and limit access
Remote Control can be disabled for improved security

Ordering Info

IRL-VAR2-i2-1	Vario2 i2, single panel, 78m, 850nm, 12V-24V AC/DC input, 10W
---------------	---

VARIO Accessories

IRL-i2-LENS-8030	VARIO i2 lens insert 80H x 30V
IRL-i2-LENS-12050	VARIO i2 lens insert 120H x 50V
IRL-WB1	Wall Bracket, L shaped
IRL-PBC-1	Pole bracket clamp for Var2-series
IRL-PBC-2	Pole bracket clamp for 2x Var2-series
VUB-WALL	Wall mount (incl. fixings)
VUB-POLE	Pole mount (incl. fixings)
IRL-VAR-RC-V1	Remote control for RayTec Vario series