

NVH-2608XRD

Video server 19", 2U, 8 bay HS, dual Xeon, SSD, RAID, RPSU

DESCRIPTION

The NVH-2608XRD is a powerful dual Xeon CPU rack-mountable VDG server. It combines top quality components and a user-friendly configuration to deliver high-power output and reliability. Its casing and components are engineered to ensure an optimized airflow (even when stacked) for higher efficiency, which results in lower energy consumption. Its redundant power supply ensures a continuous operation at all times.

FEATURES

2U High Thermal Performance Server Chassis

Dual Xeon E5 CPU

8x 3.5" hot swappableHDD bays

Standard RAID 5configuration

650W Reduntant Power Supply

2x 4-Port 12G Mini-SAS Backplane

Front access info tag for easy server management

Slide rail





The front-mounted hard-drives are configured for hot-swapping, as are the cooling fans, to ensure 24/7 operation. This means that they are easy to service and can reduce running costs. The reliability is ensured through a standard RAID 5 configuration and redundancy, but can be configured otherwise if necessary. Optionally, a hot-standby hard-drive can be configured to ensure maximum reliability and reduce service needs.

Optional expansions:


- VDG Video server storage
- NVH-GBLAN for 1 extra Ethernet connection port
- Ethernet server adapter fiber



| System | |
|--------------------------------------|---|
| Operating system | Microsoft Windows 10 Pro 64-bit |
| Hard disk | 64GB SSD (included) |
| Recording storage capacity | Up to 96TB (3.5" hard disk drives) |
| Raid configuration | Standard Raid 5 configuration |
| | Except Raid 1 configuration with 2 hard drives |
| Effective recording storage capacity | 84TB (after Raid 5) |
| Processors | 2x Intel Xeon E5 processor |
| Memory | 32GB memory |
| Network Interface | Dual Gigabit Ethernet RJ-45 (10/100/1000 MB/s) |
| Interface Advanced Management Techno | logy (AMIT) |
| Video output | VGA |
| Mechanical | |
| Form Factor | 2U 19-inch rackmount |
| Dimensions (DxWxH) | 660mm x 430mm x 88mm (26" x 16.9" x 3.5") |
| Electrical | |
| | |
| Power Input | 100-240VAC,50/60Hz 5A |
| Power Supply | 650W Redundant |
| Enviromental | |
| Operating Temperature | 5° C - 40° C (41°F - 104°F) |
| Storage Temperature | -40° C - 65° C (-40°F - 149°F) |
| Ordering Info | |
| NVH-2608XRD | Video server 19", 2U, 8 bay HS, dual Xeon, SSD, RAID, RPSU |
| Supplied Accessories | USB Compact Keyboard |
| | USB Optical Mouse |
| | Power Cord 1.5 meter |
| | Slide rail |
| | Silue rai |
| VDG Server accessories | |
| NVH-GBLAN | Extra 100/1000Mbps LAN interface |
| NVH-FIBER | Ethernet server adapter fiber |
| Basic video server storage | NVH-81TB NVH-82TB NVH-83TB NVH-84TB NVH-86TB NVH-88TB NVH-810TI |
| (incl. assembly and config) | 1TB 2TB 3TB 4TB 6TB 8TB 10TB |
| Due side second | |
| Pro video server storage | NVH-92TB NVH-94TB NVH-96TB NVH-98TB NVH-910TB NVH-912TB |
| (incl. assembly and config) | 2TB 4TB 6TB 8TB 10TB 12TB |



N V H - 2 6 0 8 X R D





FRONT





FRONT WITH OPEN HDD BAY





RELATED



Intel NVH-GBLAN

The NVH-GBLAN is a PCI Express Ethernet adapter perfect for expanding your Ethernet port(s).



WesternDigital NVH Basic Server Storage

Basic server storage for the storage environments.



WesternDigital NVH Pro Server Storage

Professional server storage for the most demanding storage environments.