

AS5710-54X

10GbE Data Center Switch

Bare-Metal Hardware

Switch Design Contributed to Open Compute Project



Product Overview

The Edge-Core AS5710-54X switch meets the high-performance, availability, and network-scaling requirements of enterprise and cloud data centers. The AS5710-54X provides full line-rate switching at Layer 2 or Layer 3 across 48 x 10GbE ports and 6 x 40GbE uplinks. The switch can be deployed either as a Top-of-Rack switch, or as part of a 10GbE or 40GbE distributed spine, forming a non-blocking folded CLOS data center fabric. The switch is rack mountable in either a standard 19 inch rack, or with the Open Rack Switch Adapter in the 21 inch Open Rack.

The AS5710-54X hardware provides the high availability features required for data center operation, including; redundant, hot-swappable AC or -48VDC PSUs or 12VDC power input; fan tray with 4+1 redundant fans; and port-to-power or power-to-port airflow options. The AS5710-54X is an ideal Top-of-Rack switch for virtualized data centers, with its support of VXLAN and NVGRE tunneling functions in hardware.

Key Features and Benefits

- Cost-effective, bare-metal switch infrastructure for data center fabric.
- 48 x SFP+ switch ports, supporting 10GbE (DAC, 10GBASE-SR/LR) or 1GbE (1000BASE-T/SX/LX).
- 6 x 40 QSFP switch ports, each supporting 40GbE (DAC, 40GBASE-SR4/LR4) or 4 x 10GbE (DAC or fiber breakout cable).
- Port Grouping to group 4 x 10G ports into one 40G port at the physical layer for maximum bandwidth utilization, and for 300m optical reach over MMF.
- Full line-rate Layer 2 or Layer 3 forwarding of 1.44Tbps.
- VXLAN and NVGRE tunneling support in hardware for network virtualization.
- Rack mountable in standard 19" racks. Mountable in 21" Open Rack with the Open Rack Switch Adapter.
- Supports hot/cold aisle with port-to-power and power-to-port airflow SKUs.
- All ports on front; PSUs, fan tray on rear.
- Hot-swappable, load sharing, redundant AC or -48VDC PSUs. 12VDC power input option.
- Hot swappable 4+1 redundant fans.
- Management: Ethernet and console RJ-45 ports; USB storage port.
- Hardware switch pre-loaded with Open Network Install Environment (ONIE) for automated loading of compatible independent SwitchOS software.
- Compatible with Cumulus® Linux® r2.2.1 and later SwitchOS software from Cumulus Networks™.
- Compatible with Switch Light OS from Big Switch Networks.
- CPU and memory subsystem provided on factory-pluggable internal module for flexibility
 - AS5710-54X SKUs with Freescale P2041 processor
 - AS5712-54X SKUs with Intel™ Atom® C2538 x86 processor

Features

Ports

Switch Ports:
48 x SFP+ each supporting 10GbE or 1GbE
6 x QSFP each supporting 40GbE or 4 x 10GbE
Management Ports on Front Panel:
1 x RJ-45 serial console
1 x RJ-45 100/1000BASE-T management
1 x USB Type A storage port

Key Components

Switch Silicon: Broadcom BCM56854 Trident II 720Gbps CPU
AS5710-54X SKUs have CPU Module with
Freescale P2041 quad-core 1.5GHz CPU
Memory: 2GB DDR3 SDRAM with ECC
Flash: 128MB NOR, 2GB NAND, 8GB SD Card
AS5712-54X SKUs have CPU Module with:
Intel Atom C2538 quad-core 2.4GHz x86 processor
Memory: 8GB SODIMM DDR3 RAM with ECC
Flash: 16MB SPI, 8GB NAND

Performance

Wire Speed Forwarding: L2 and L3
Switching Capacity: 1.44Tbps Forwarding Rate: 1Bpps
MAC Addresses: 320K
VLAN IDs: 4K
Jumbo frames (9216Bytes)
L3 Routes: IPv4 64K, IPv6 20K
Packet Buffer Size: 12MB shared buffer pool
Latency (RFC2544): 720 ns (L2/L3, cut thru, full line rate)

LEDs

10G SFP+ Port LEDs: Link Speed, Link Status, Activity
40G QSFP Port LEDs: Link Status, Activity for 40G status
40G QSFP Breakout LEDs: set of 24 LEDs, 4 per QSFP port,
show Link, Status, Activity 10G links with 4x10G breakout
Ethernet Management Port LED: Link Status, Activity
Console Port LED: Link Status
System LEDs: PSU1, PSU2, Diagnostic, Fans, Locator

Supported Optics and Cables

SFP+ Ports:
10GBASE-CR DAC: up to 5m passive; up to 10m active
10GBASE-SRL/SR: up to 100/300m over OM3 MMF
10GBASE-LR: Up to 10km over SMF 10GBASE-
1000BASE-SX, 1000BASE-LX, 100/1000BASE-T
QSFP Ports:
40GBASE-CR4 DAC; 0.5m to 7m; Passive and Active
40GBASE-CR4 DAC to 4 x SFP+ 10GBASE-CR DAC;
up to 5m passive; up to 10m active
40GBASE-SR4: Up to 100m over OM3 MMF, 150m over
OM4 MMF
40GBASE-SR4 to 6 x 10GBASE-SR: 100m over OM3, 150m
OM4
40GBASE-LR4: Up to 10km over SMF

Software

Switch is loaded with Open Network Install Environment (ONIE)
software installer
Compatible with the following switchOS software:
AS5710-54X is compatible with Switch Light OS from Big
Switch Networks, and their Big Tap and Big Cloud
applications
AS5712-54X is compatible with Cumulus Linux r2.2.1 and
later

Physical and Environmental

Dimensions (WxDxH): 443 x 473 x 43.4mm (17.4 x 18.6 x 1.71
in)
Weight: 8.5kg (18.74lbs), with two installed PSU modules
Fans: hot-swappable 4+1 redundant fans
Operating Temperature: 0°C to 40°C (32°F to 104°F)
Storage Temperature: -40°C to 70°C (-40°F to 158°F)
Operating Humidity: 5% to 95% non-condensing

Power

PSUs: 2 redundant, load-sharing, hot-swappable AC or -48VDC
Input Voltage: 90 to 264VAC at 50-60Hz. -48 to -72VDC.
Input Current: Max 6A @100/120VAC, 3A @200/240VAC,
10A @-72VDC
PSU Efficiency: Up to 93% for AC PSUs
12VDC power input option

Regulatory

EMI
CE Mark (EN55022 Class A)
FCC Part 15 Class A
VCCI
Safety
CB, EN 60950
UL/CUL
Environmental: Temperature: IEC 68-2-14
Drop: ISTA 2A
RoHS-6 Compliant

Warranty

Please check www.edge-core.com for the warranty terms in
your country. The warranty provides return-to-factory hardware
replacement for a three year period in North America.

For More Information

To find out more about Edge-Core Networks products and
solutions, visit www.edge-core.com.

About Edge-Core Networks

Edge-Core Networks is in the business of providing innovative
network solutions. In the service provider network, in the data
center or in the cloud, Edge-Core Networks delivers the software
and systems that transform the way the world connects.
Edge-Core Networks serves customers and partners worldwide.
Additional information can be found at www.edge-core.com.

Edge-Core Networks is a subsidiary of Accton Technology
Corporation, the leading network ODM company. The
Edge-Core data center switches are developed and
manufactured by Accton.

To purchase Edge-Core solutions, please contact your
Edge-Core Network representatives at +886 3 563 8888 (HQ)
or +1 (877) 828-CORE (877-828-2673) or authorized resellers.

© Copyright 2014 Edge-Core Networks Corp. The information contained herein is subject to change without
notice. This document is for informational purposes only and does not set forth any warranty, expressed or
implied, concerning any equipment, equipment feature, or service offered by Edge-Core Networks. Edge-Core
Networks shall not be liable for technical or editorial errors or omissions contained herein.

Ordering Information

5710-54X-O-AC-F-US	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual AC PSUs, port-to-power airflow, N. America
5710-54X-O-AC-B-US	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual AC PSUs, power-to-port airflow, N. America
5710-54X-O-AC-F-EU	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual AC PSUs, port-to-power airflow, Europe
5710-54X-O-AC-B-EU	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual AC PSUs, power-to-port airflow, Europe
5710-54X-O-AC-F-UK	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual AC PSUs, port-to-power airflow, UK
5710-54X-O-AC-B-UK	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual AC PSUs, power-to-port airflow, UK
5710-54X-O-AC-F-JP	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual AC PSUs, port-to-power airflow, Japan
5710-54X-O-AC-B-JP	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual AC PSUs, power-to-port airflow, Japan
5710-54X-O-48V-F	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual 48VDC PSUs, port-to-power airflow
5710-54X-O-48V-B	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, dual 48VDC PSUs, power-to-port airflow
5710-54X-O-12V-F	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, one 12VDC power input, port-to-power airflow
5710-54X-O-12V-B	AS5710-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Freescale P2041 processor, ONIE software installer, one 12VDC power input, power-to-port airflow
5712-54X-O-AC-F-US	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual AC PSUs, port-to-power airflow, N. America
5712-54X-O-AC-B-US	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual AC PSUs, power-to-port airflow, N. America
5712-54X-O-AC-F-EU	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual AC PSUs, port-to-power airflow, Europe
5712-54X-O-AC-B-EU	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual AC PSUs, power-to-port airflow, Europe
5712-54X-O-AC-F-UK	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual AC PSUs, port-to-power airflow, UK

Ordering Information

5712-54X-O-AC-B-UK	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual AC PSUs, power-to-port airflow, UK
5712-54X-O-AC-F-JP	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual AC PSUs, port-to-power airflow, Japan
5712-54X-O-AC-B-JP	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual AC PSUs, power-to-port airflow, Japan
5712-54X-O-48V-F	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual 48VDC PSUs, port-to-power airflow
5712-54X-O-48V-B	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, dual 48VDC PSUs, power-to-port airflow
5712-54X-O-12V-F	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, one 12VDC power input, port-to-power airflow
5712-54X-O-12V-B	AS5712-54X 48-Port 10G SFP+ with 6x40G QSFP uplinks, CPU Module with Intel Atom C2538 processor, ONIE software installer, one 12VDC power input, power-to-port airflow
PSU-AC-400-F	400W AC Power Supply FRU, port-to-power airflow, no power cord
PSU-AC-400-B	400W AC Power Supply FRU, power-to-port airflow, no power cord
PSU-48V-400-F	400W -48V DC Power Supply FRU, power-to-port airflow, no power cord
PSU-48V-400-B	400W -48V DC Power Supply FRU, port-to-power airflow, no power cord
PSU-12V-400-1	12V DC power input unit FRU
FAN-1U-1x1D-F	Fan Tray FRU, port-to-power airflow
FAN-1U-1x1D-B	Fan Tray FRU, power-to-port airflow
CBL-PWR-US	AC Power Cable - US (125V/13A, 1830mm)-- only required with spare power supplies
CBL-PWR-EU	AC Power Cable - Europe (250V/10A, 1830mm)-- only required with spare power supplies
CBL-PWR-UK	AC Power Cable - UK (250V/10A, 1830mm)-- only required with spare power supplies
CBL-PWR-JP	AC Power Cable - Japan-- only required with spare power supplies
5710-54X-SVC-RTF	AS5710-54X Annual Hardware Service, post warranty, Return-to-Factory
ORSA-1U	Open Rack Switch Adapter, for mounting standard 19 inch form factor 1U switches into 21 inch Open Rack